



800 2T Factory Line ROAD RACING

Road Racing Grand Prix Lubricant

Premix Racing 2 stroke Engines

100% Synthetic – **ESTER Core®** Technology

TYPE OF USE

Formula developed for Road Racing Grand Prix Teams. Suitable for all kind of gasoline up to 124 octane.

All racing premix 2 stroke engines fitted on Racing bikes and operating at high revs and under high load.

For moto-cross, use MOTUL 800 2T OFF ROAD. For oil injector systems, use MOTUL 710 2T.

PERFORMANCES

STANDARDS : Above all Standards

ESTER Core® TECHNOLOGY

For decades MOTUL has developed high performance synthetic Ester based lubricants.

By selecting esters over other high performance synthetic base stocks and combining them with an innovative additive package, MOTUL has created a perfect synergy.

This most advanced **ESTER Core®** Technology allows maximum power output of the engine without compromising reliability and wear.

Allow a perfect lubrication when running on wet weather conditions.

Very high lubricating properties for low friction and wear.

Keeps engines and exhaust power valves clean and well lubricated.

Prevents piston rings and exhaust power valves from sticking.

RECOMMENDATIONS

Mixing ratio: ROAD RACING GRAND PRIX from 3% to 4% (from 33:1 to 25:1)

In normal conditions decrease the percentage by 0.5%.

Adjust according to your own use.

PROPERTIES

Color	Visual	Orange
Density at 20°C (68°F)	ASTM D1298	0.927
Viscosity at 40°C (104°F)	ASTM D445	157.4 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	19.2 mm ² /s
Viscosity Index	ASTM D2270	140
Flash point	ASTM D92	274°C / 525°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 – Fax : 33 1 48 33 28 79 – Web Site: www.motul.com